

Non-Bubbling Kneader



**NON-BUBBLING
KNEADER NBK-1**

To knead high-viscosity material in a short time without bubbles. It is easy to clean the machine because it has no cutting shaft/hook/blending blades. It is possible to keep the mixed materials in containers as storages. Safety devices such as Door-lock, unbalance-detector or when over-loaded are installed. The same operation is possible to be done by just one-touch with the timer setting. It generates low shaking and noise during operation due to the compact structure and good balance. The operation procedure is very simple and easy for anybody. It is very efficient to operate with 2 containers at one time. Just put materials into 2 containers and push the Start Button. The materials are processed in a short time. High-speed revolution and self-turning containers make the working materials be homogeneously kneaded without generating bubbles in planetary motions which cause turbulent flow in the containers.

Specification:

Model No.	NBK-1
1) Capacity:	120mL (polyethylene)
2) Normal Vol.:	About 70mLx2
3) Rpm (no load):	Revolution max. 2,000rpm Ratio to self-turn 3:1
4) Timer:	1-15min. or continuous
5) Safety device:	Door lock switch; Automatic stop when unbalanced or over-loaded
6) Power source:	AC100V 50/60Hz or AC115V 60Hz
7) Power consumption:	200VA
8) Dimensions:	260W x 335D x 275H mm
9) Weight:	About 12kg
10) Accessories:	Fixed roller x 1, Grease x 1
*Option:	Adaptor for Teflon-coated container Adaptor for syringe Order-made adaptor (material to be defined) Kneading balls